







Certificate of conformity of the factory production control No. 3592/2019

Inspecta Latvia has granted this certificate as proof that

Precast concrete products:

Solid slabs, series "MP" and "SP", according to Annex

PRODUCED BY:

SIA "DAUGAVPILS DZELZSBETONS"

Rūpniecības iela 1A, Daugavpils, LV-5420; Reg. No. 41503019513

ADDRESS OFTHE MANUFACTURING PLANT: SIA "Daugavpils dzelzsbetons", Rūpniecības iela 1A, Daugavpils, LV-5420

CERTIFIED ACCORDING:

Certification scheme, based on initial inspection of the manufacturing plant and of factory production control, continuing surveillance, assessment and evaluation of factory production control.

PRODUCT COMPLIES WITH THE REQUIREMENTS OF STANDARD:

LVS EN 13369:2018

"Common rules for precast concrete products" declared properties: concrete compressive strength, durability, reinforcing/prestressing steel, fire resistance and detailing of product.

This certificate was first issued on 4 February 2019 and will remain valid as long as neither the standard, the construction product, nor the manufacturing conditions in the plant are modified significantly.

Mārtiņš Maskavs

Certification Manager

45 Inspects

Certificate issued on 1 (one) page with the Annex on 1 (one) page

EN ISO/IEC 17065 S1-182 AS Inspecta Latvia Skanstes iela 54A, Rīga LV-1013, Latvija

T. +371 67 607 900 F. +371 67 607 901 latvia@kiwa.com

www.kiwa.com/lv

Inspecta Latvia Trust, Quality & Progress



Product: solid slabs, series "MP".

Characteristics	Declared properties of product		
	min	max	
Type (code)	series	series "MP"	
Concrete Compressive strength, N/mm²	C25/30	C50/60	
Reinforcing steel Ultimate tensile strength, N/mm² Tensile yield strength, N/mm²	525 550		
Durability of product Freeze resistance (F), cycles Exposure class		300 FX3	
Fire resistance (R), min	Tabulated data	Tabulated data (EN 1992-1-2)	
Detailing of product	According to de	According to design specification	

Product: prestressed solid slabs, series "SM".

Characteristics	Declared properties of product		
	min	max	
Type (code)	serie	series "SM"	
Concrete			
Compressive strength, N/mm ²	C25/30	C50/60	
Prestressing reinforcement			
Tensile strength (fpk), N/mm ²	1770		
Tensile yield strength (fp0.1k), N/mm ²	1500		
Durability of product			
Freeze resistance (F), cycles		200	
Exposure class		XC2+XF2	
Fire resistance (R), min	Tabulated dat	Tabulated data (EN 1992-1-2)	
Detailing of product	According to de	According to design specification	

Mārtiņš Maskavs

Certification Manager

as institucija



T. +371 67 607 900 F. +371 67 607 901 latvia@kiwa.com

